

# Product Specifications

540EZDFV2

7-16 DIN Female EZfit<sup>®</sup> for 1/2 in FXL-540 cable



## CHARACTERISTICS

### General Specifications

---

Interface	7-16 DIN Female
Body Style	Straight
Brand	EZfit <sup>®</sup>
Mounting Angle	Straight

### Electrical Specifications


---

Connector Impedance	50 ohm
Operating Frequency Band	0 – 7500 MHz
Cable Impedance	50 ohm
3rd Order IMD	-115 dBm @ 1890 MHz
3rd Order IMD Test Method	Two +43 dBm carriers
RF Operating Voltage, maximum (vrms)	1980.00 V
dc Test Voltage	4000 V
Outer Contact Resistance, maximum	1.50 mOhm
Inner Contact Resistance, maximum	0.80 mOhm
Insulation Resistance, minimum	5000 MOhm
Average Power	1.0 kW @ 900 MHz
Peak Power, maximum	40.00 kW
Insertion Loss, typical	0.05 dB
Shielding Effectiveness	-110 dB

# Product Specifications

540EZDFV2

## Outline Drawing



## Mechanical Specifications

Outer Contact Attachment Method	Clamp   Tool-flare
Inner Contact Attachment Method	Captivated
Outer Contact Plating	Trimetal
Inner Contact Plating	Silver
Attachment Durability	25 cycles
Interface Durability	500 cycles
Interface Durability Method	IEC 61169-4:9.5
Connector Retention Tensile Force	1112 N   250 lbf
Connector Retention Torque	4.00 N-m   2.95 ft lb
Insertion Force	200.17 N   45.00 lbf
Insertion Force Method	IEC 61169-1:15.2.4
Pressurizable	No

## Dimensions

Nominal Size	1/2 in
Diameter	29.00 mm   1.14 in
Length	57.35 mm   2.26 in
Weight	87.79 g   0.19 lb

## Environmental Specifications

[www.commscope.com/andrew](http://www.commscope.com/andrew)

# Product Specifications



540EZDFV2

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Immersion Depth	1 m
Immersion Test Mating	Mated
Immersion Test Method	IEC 60529:2001, IP68
Water Jetting Test Mating	Mated
Water Jetting Test Method	IEC 60529:2001, IP66
Moisture Resistance Test Method	MIL-STD-202F, Method 106F
Mechanical Shock Test Method	MIL-STD-202, Method 213, Test Condition I
Vibration Test Method	IEC 60068-2-6
Corrosion Test Method	MIL-STD-1344A, Method 1001.1, Test Condition A

## Standard Conditions

---

Attenuation, Ambient Temperature	20 °C   68 °F
Average Power, Ambient Temperature	40 °C   104 °F

## Return Loss/VSWR

---

Frequency Band	VSWR	Return Loss (dB)
50–1000 MHz	1.03	36.00
1000–1900 MHz	1.03	36.00
1900–2200 MHz	1.04	34.00
2200–2700 MHz	1.05	33.00
2700–3600 MHz	1.11	26.00
3600–6000 MHz	1.25	19.00
6000–8000 MHz	1.29	18.00

## \* Footnotes

---

Immersion Depth	Immersion at specified depth for 24 hours
Insertion Loss, typical	$0.05\sqrt{\text{freq}}$ (GHz) (not applicable for elliptical waveguide)