

TeleDelta HDS2800 Series

HDS2803-JJR - Quad HDMI/YPbPR/CVBS Input, DVB-T/IP/ASI Output



Rear Panel Photo

4x Selectable HDMI/YPbPR/CVBS Input, 2 x DVB-T/IP/ASI Outputs

The latest addition to the TeleDelta HDS2800 series is the HDS2803-JJR configuration. The non-modular HDS2803-JJR has a combination of 4x HDMI, YPbPr, CVBS Inputs per 1RU frame, allowing installers to pick and choose their input options up to a maximum of 4 inputs per chassis.

The HDS2803-JJR, utilises the HDS2803 chassis providing selectable MPEG-2 or MPEG-4/H.264 encoding and selectable bitrates per input channel. The HDS2803 chassis also provides 2x Independent, fully configurable COFDM DVB-T output carriers per chassis.

The TeleDelta designed user interface and control software allows installers to configure and save their desired setup parameters for quick and easy setups onsite.

Key Features HDS2803-JJR

- Selectable 4x HDMI/YPbPr/CVBS Inputs
- Supports Full HD 1080P (MPEG4)
- MPEG-2 or MPEG-4 /H.264 Encoding
- Selectable Bit-rate encoding
- 2x Independent COFDM DVB-T Outputs
- Configurable IP data output (IPTV)
- Compact 1RU chassis
- TeleDelta Web-based Management
- ASI Input / Output options available

Common Applications

- In-venue Digital TV delivery
- PayTV Content Delivery
- Hotels, Hospitals and Churches
- Education and Universities
- Corporate / Enterprise
- Broadcast Head-ends
- Security Control Rooms
- Audio Video Installations
- IPTV streaming

For more information and ordering please visit www.teledelta.com or contact your distributor for pricing.

For more information please contact your local distributor or sales@teledelta.com

